

Pos.	Quantity	Object	Single unit price	Total price
		<p><b>Flexible- Flanged-Ductconnectors/Compensator</b> for expansion-joints and soundbreaking, suitable for smoke exhaust ducts with general approval by Gov. building authorities.</p> <p>Consisting of a bellows of special airtight coated fabric, durable and tightly connected to two stable, round-edged flange-bars with prepunched holes in corner-fittings, suitable to fit all standard duct supporting frames. Flanges galvanised, with circular seams along edges for the insertion of a sealing-strip - stitched to bellow.</p> <p>Airtight according to German Standard DIN 24194 &amp; VDI 3803.</p> <p>Bellow: In essential parts <b>incombustible</b>, high temperature resistant, <b>resistant against smoke gases</b>, consisting of HT-high temperature mineral heat protecting fabric (melting point 1700°C Airtight heat resistand coating, pressure resistant, flexible.</p> <p>Stable section through supporting frame.</p> <p>Certified DIN 18232-6 / EN1366-8 with general approval by Gov. building authorities.</p> <p>Temperature resistant: 600 °C for 120 min</p> <p>Type: <b>FFD-600 HO DIN 18232-6 / EN 1366-8 Burgert-Acustiflex</b></p> <p>Available in any required dimension for round or rectangular sections.</p> <p>Dimensions:  clear length x width: _____ x _____(mm)  or  inside diameter .....: _____(Ømm)  width when stretched (WS)*.....: _____ (mm)  flexible range (FR) **.....: _____ (mm)</p> <p>* WS = width when mounted + 20 mm, but not under 150mm  ** FR = width when mounted till WS 0,6</p>		